

TDC Power Products Co.,Ltd

DA-20-06

INPUT VOLTAGE **120VAC**

OUTPUT VOLTAGE **6VAC**


ELECTRICAL & MECHANICAL SPECIFICATION



ELECTRONICAL SPECIFICATION

Input Voltage	120	Volts
Frequency (Hz)	60	Hz
Power Rated (W)	28	W
Exciting Current With No load	90	mA Max
Exciting Current With Full load	250	mA Max
Output Voltage	6.0	Volts±5%
Output Current	3.33	Amp
Output Voltage Without Load	7.0	Volts±5%
HI-POT :		
Test Time	1	Min
PRI TO SEC	1250	Volts
PRI TO CORE	1250	Volts
SEC TO CORE	1250	Volts
Efficiency	70	%
Insulation Class	B (130)	°C

隔板:31*26.5cm
CARTON:32*27.5*13.5cm



MECHANICAL SPECIFICATION

Dimensions (L*W*H)	81.5*56.5*48.5	mm
Weight	440	g
Environment:		
Operating Temperature	-10 To 40	°C
Storage Temperature	-20 To 70	°C
Relative Temperature	40°C±2°C	
RELATIVE HUMIDITY	90% RH	

Output Cable: **5.5*2.1 FEMALE CONNECTOR**

ELECTRICAL CIRCUIT

