


TDC Power Products Co.,Ltd

DE-60-15W


INPUT VOLTAGE **230VAC**
OUTPUT VOLTAGE **15VAC**

ELECTRICAL & MECHANICAL SPECIFICATION



OUTPUT CONNECTOR
2.35φ FEMALE CONNECTOR

INPUT POWER CORD:
VDE H05RN-F 2*0.75mm²
+IP44 PLUG



Input Cable: **VDE H05RN-F 2*0.75mm²
2.0M LENGTH+IP44 PLUG**

Output Cable: **2.35 φ FEMALE CONNECTOR**

ELECTRONICAL SPECIFICATION

Input Voltage	230	Volts
Frequency (Hz)	50	Hz
Power Rated (W)	70	W
Exciting Current With No load	110	mA Max
Exciting Current With Full load	330	mA Max
Output Voltage	15.0	Volts±5%
Output Current	4.0	Amp
Output Voltage Without Load	17.1	Volts±5%

HI-POT :

Test Time	1	Min
PRI TO SEC	3750	Volts
PRI TO CORE	3750	Volts
SEC TO CORE	1250	Volts
Efficiency	70	%
Insulation Class	B (130)	°C


MECHANICAL SPECIFICATION

Dimensions (L*W*H)	101.5*63.5*74.0	mm
Weight	1400	g
Environment:		
Operating Temperature	-10 To 40	°C
Storage Temperature	-20 To 70	°C
Relative Temperature	40°C±2°C	
RELATIVE HUMIDITY	90% RH	

ELECTRICAL CIRCUIT

T'FUSE:250V/2A130°C

INPUT:
230Vac 50Hz



OUTPUT:
15Vac 60VA

Transformer