

TDC Power Products Co.,Ltd

DE-60-24W

INPUT VOLTAGE **230VAC**

OUTPUT VOLTAGE **24VAC**

ELECTRICAL & MECHANICAL SPECIFICATION




ELECTRONICAL SPECIFICATION

Input Voltage	230	Volts
Frequency (Hz)	50	Hz
Power Rated (W)	70	W
Exciting Current With No load	110	mA Max
Exciting Current With Full load	330	mA Max
Output Voltage	24.0	Volts±5%
Output Current	2.5	Amp
Output Voltage Without Load	27.4	Volts±5%


HI-POT :

Test Time	1	Min
PRI TO SEC	3750	Volts
PRI TO CORE	3750	Volts
SEC TO CORE	1250	Volts
Efficiency	70	%
Insulation Class	B (130)	°C



OUTPUT CONNECTOR
2.35φ FEMALE CONNECTOR

INPUT POWER CORD:
VDE H05RN-F 2*0.75mm²
+IP44 PLUG



MECHANICAL SPECIFICATION

Dimensions (L*W*H)	101.5*63.5*74.0	mm
Weight	1400	g
Environment:		
Operating Temperature	-10 To 40	°C
Storage Temperature	-20 To 70	°C
Relative Temperature	40°C±2°C	
RELATIVE HUMIDITY	90% RH	


Input Cable: **VDE H05RN-F 2*0.75mm²
2.0M LENGTH+IP44 PLUG**

Output Cable: **2.35 φ FEMALE CONNECTOR**

ELECTRICAL CIRCUIT

T'FUSE:250V/2A130°C

INPUT:
230Vac 50Hz



OUTPUT:
24Vac 60VA

Transformer